



Dimensions	310mm x 310mm x 500mm (h)	12.2in x 12.2in x 19.69in (h)	
Weight	21,4 kg	47,2 lb	
Voltage-Frequency	230V - 50Hz	230V - 60Hz	115V - 60Hz
Current Consumption	2,9 A	4,4 A	
Compressor Power	1/3 HP		
Power Consumption (Cooling)	440 W	1500 Btu\h	
Power Consumption (Heating)	400 W	1365 Btu\h	
Cooling Capacity *	930 W	3175 Btu\h	
Minimum Water Flow	600 lh	160 Usgal\h	
Air Flow	215 m <sup>3</sup> \h	7600 CFH	
Maximum Exchanger's Pressure	0,6 bar	8,7 PSI	
Ambient Temperature Range	5°C - 38°C	32°F - 100°F	
Certification	CE		
Protection Grade	IPX4		
* the value reported refers to the following condition: room temperature 30°C (86°F), w ater temperature 25°C (77°F)			

Material:	Drawing: TK 2000 – technical data		
Thickness:	File: TK_2000_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1:6	Date: 24/10/2014
Approved:	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 <a href="http://www.tecoonline.com">http://www.tecoonline.com</a>		
	Drawer: Matteo		