

Trickle Filters for Aquariums & Aquaculture - Wet Dry Filtration

Trickle Filter Model	Diameter (mm)	Height (mm)	Inlet Size (mm)	Outlet Size (mm)	Trickle Standpipe Level (mm)	Degas Blower Inlet Size (mm)	Max Flow Rate (m <sup>3</sup> /h)	TAN Removal Rate with BM-500 (gr/TAN/day)	Max BM-500 Media (m <sup>3</sup> )	Body Material	BIOMEDIA	OVERFLOW SWITCH
MAT T-500	500	1422	90	90	1172	25	7	54	0.18	PP	OPTIONAL	OPTIONAL
MAT T-750	750	1768	140	140	1518	32	25	150	0.5	PP	OPTIONAL	OPTIONAL
MAT T-1000	950	1835	225	225	1585	40	75	220	0.9	PP	OPTIONAL	OPTIONAL
MAT T-1250	1250	2095	250	250	1845	50	115	517.99	1.73	PP	OPTIONAL	OPTIONAL
MAT T-1500	1500	2509	280	280	2259	50	145	900	3	PP	OPTIONAL	OPTIONAL
MAT T-2000	2000	2429	315	315	2179	63	400	1560	5.2	PP	OPTIONAL	OPTIONAL
MAT T-3000	3000	2810	450	450	2560	63	1100	3840	12.8	PP	OPTIONAL	OPTIONAL